



Specification



- Handle
Zinc die-cast
- Insert and screw
Steel, blackened
- Plastic coated
 - **SW** black, RAL 9005, textured finish
 - **OS** orange, RAL 2004, textured finish
 - **RS** red, RAL 3000, textured finish
 - **SR** silver, RAL 9006, textured finish
 - **CR** chrome-plated
 - **RH** uncoated
- RoHS compliant

On request

- Call our sales staff for pricing and delivery on your special modification requirements.

Information

GN300 Adjustable hand levers are the result of modern industrial design.

All such levers have proven to be ideal wherever parts have to be clamped in a confined space or in a particular lever position. The insert is connected to the lever via serrations which can be easily be disengaged.

Pulling the lever upwards, disengages the serrations, allowing it to be swivelled to the ideal clamping position.

When releasing the lever, the serrations automatically re-engage.

see also...

- *Adjustable Levers with Secure Clamping Force GN 300.4 (with increased clamping force and screw) → page XYZ*
- *Zinc Die-Cast Adjustable Levers with Push Button GN 303 (with push button and screw) → page XYZ*
- *Zinc Die-Cast Adjustable Levers GN 300 (with female thread) → page XYZ*
- *Zinc Die-Cast Adjustable Levers GN 300.1 (with Stainless Steel screw) → page XYZ*
- *Stainless Steel Adjustable Levers GN 300.5 (with screw) → page XYZ*
- *Straight Zinc Die-Cast Adjustable Levers GN 302 (with screw) → page XYZ*

How to order	
1	l ₁
2	d ₁
3	l ₂
4	Color (Finish)

300-30-10X32-10-SW

Metric table

Dimensions in: millimeters - inches

I ₁	d ₁ Thread		I ₂ Thread length								d ₃	d ₄	h ₁	h ₂	h ₃	h ₄ Stroke
				6	8	10	12	16								
30 1.18	M 3	-	6 .24	8 .31	10 .39	12 .47	16 .63				10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14
30 1.18	M 4	-	12 .47	16 .63	20 .79	25 .98	32 1.26				10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14
30 1.18	M 5	M 6	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97		10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14
45 1.77	M 4	-	12 .47	16 .63	20 .79	25 .98	32 1.26				10 .39	13 .51	24.5 .96	4 .16	34 1.34	3.5 .14
45 1.77	M 5	M 6	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97		10 .39	13 .51	24.5 .96	4 .16	34 1.34	3.5 .14
63 2.48	M 6	M 8	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	13.5 .53	17.5 .69	31 1.22	6.5 .26	45 1.77	4 .16
63 2.48	M 10	-	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15		13.5 .53	17.5 .69	31 1.22	6.5 .26	45 1.77	4 .16
78 3.07	M 8	M 10	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	16 .63	21 .83	36 1.42	8 .31	54 2.13	4 .16
78 3.07	M 12	-	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15			16 .63	21 .83	36 1.42	8 .31	54 2.13	4 .16
92 3.62	M 10	M 12	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	19 .75	24 .94	43 1.69	11 .43	64 2.52	4 .16
92 3.62	M 16	-	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15			19 .75	24 .94	43 1.69	11 .43	64 2.52	4 .16
108 4.25	M 12	M 16	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	120 4.72		23 .91	30 1.18	50.5 1.99	12 .47	75 2.95	5 .20

Inch table

Dimensions in: inches - millimeters

I ₁	d ₁ Thread		I ₂ Thread length								d ₃	d ₄	h ₁	h ₂	h ₃	h ₄ Stroke	
				.39	.47	.63											
1.18 30	10 x 32 10 x 32		.39 10	.47 12	.63 16						.39 10	.51 13	.96 24.5	.16 4	1.22 31	.14 3.5	
1.18 30	10 x 24 10 x 24		.47 12	.63 16	.79 20	.98 25	1.26 32				.39 10	.51 13	.96 24.5	.16 4	1.22 31	.14 3.5	
1.18 30	1/4 x 20 1/4 x 20		.39 10	.47 12	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	.39 10	.51 13	.96 24.5	.16 4	1.22 31	.14 3.5	
1.77 45	10 x 32 10 x 32		.39 10	.47 12	.63 16	.79 20	.98 25	1.26 32			.39 10	.51 13	.96 24.5	.16 4	1.34 34	.14 3.5	
1.77 45	10 x 24 10 x 24		.47 12	.63 16	.79 20	.98 25	1.26 32				.39 10	.51 13	.96 24.5	.16 4	1.34 34	.14 3.5	
1.77 45	1/4 x 20 1/4 x 20		.39 10	.47 12	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	.39 10	.51 13	.96 24.5	.16 4	1.34 34	.14 3.5	
2.48 63	1/4 x 20 1/4 x 20		.47 12	.63 16	.79 20	.98 25					.53 13.5	.69 17.5	1.22 31	.26 6.5	1.77 45	.16 4	
2.48 63	5/16 x 18 5/16 x 18		.47 12	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	.53 13.5	.69 17.5	1.22 31	.26 6.5	1.77 45	.16 4
2.48 63	3/8 x 16 3/8 x 16		.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	.53 13.5	.69 17.5	1.22 31	.26 6.5	1.77 45	.16 4	
3.07 78	3/8 x 16 3/8 x 16		.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	.63 16	.83 21	1.42 36	.31 8	2.13 54	.16 4	
3.07 78	1/2 x 13 1/2 x 13		.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	1.97 50		.63 16	.83 21	1.42 36	.31 8	2.13 54	.16 4	

Inch table

Dimensions in: inches - *millimeters*

1 l₁	2 d₁ Thread	3 l₂ Thread length									d₃	d₄	h₁	h₂	h₃	h₄ Stroke
3.62 92	3/8 x 16 3/8 x 16	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63		.75 19	.94 24	1.69 43	.43 11	2.52 64	.16 4
3.62 92	1/2 x 13 1/2 x 13	.63 16	.79 20	.98 25	1.26 32	1.38 35	1.57 40	1.77 45	1.97 50	2.48 63	.75 19	.94 24	1.69 43	.43 11	2.52 64	.16 4
4.25 108	1/2 x 13 1/2 x 13	.98 25	1.26 32	1.57 40	1.97 50	2.17 55	2.48 63				.91 23	1.18 30	1.99 50.5	.47 12	2.95 75	.20 5
4.25 108	5/8 x 11 5/8 x 11	1.26 32	1.57 40	1.97 50	2.17 55	2.48 63					.91 23	1.18 30	1.99 50.5	.47 12	2.95 75	.20 5